

Proven motion-compensated gangway for safe, efficient offshore transfers

As the core system in the Safeway rental fleet, the **Seagull** delivers proven performance and flexibility for short- and long-term offshore campaigns.

Engineered for reliability, efficiency, and comfort, it combines field-proven hydraulic-electric technology with the highest workability in its class. With more than ten units operating worldwide, the Seagull has earned its reputation as the preferred “plug-and-play”

Walk-to-Work system for PSV and OCV operations.

PSV / OCV retrofit

Drive:	Electro-hydraulic
Reach:	Vertical ± 16 m / Horizontal ± 28 m
Capacity:	2-3-6 pax / 1000 kg cargo
Profile:	Proven, versatile rental system

Key Features

- **Heavy-duty system** for medium to large offshore vessels
- **Workability up to Hs 3.5 m**, enabling year-round operations
- **Hover and float modes** for safe, flexible landings
- **Integrated 3D hoist up to 1000 kg** for cargo and hose handling
- **Supports liquid transfer operations** (grout, water, fuel, etc.)
- **Low energy consumption (< 100 kW)** with electro-hydraulic drive
- **Roll compensation** for high performance
- **Full gangway enclosure** for weather-protected personnel transfer
- **Ship to ship operations** without modification to structure
- **Class approved (BV)** and field-proven with leading offshore contractors



Reliable. Flexible. Field-proven.

With its exceptional performance and low energy footprint, the Safeway Seagull remains the trusted rental choice for safe and efficient offshore access, setting the benchmark for Walk-to-Work performance worldwide.



Hover mode



Gangway cover

Technical Specifications **Safeway Seagull**

Parameter	Specification
Bridge length (min / max)	18 m / 28 m
Vertical elevation stroke	10 m
Vertical range incl. luffing ($\pm 15^\circ$)	17 m
Bridge width (inside inner boom)	≥ 1.1 m
Bridge height (inside)	2.2 m
Max roll compensation	$\pm 12.5^\circ$
Weight (excl. HPU)	~ 90000 kg
Power consumption (active / passive)	85 kW / 25 kW
Power supply	440 V or 690 V / 3 ph / 60 Hz
Workability	$H_s = 3.5$ m ($L_{pp} = 75$ m vessel)
Temperature range	- 20 °C to + 55 °C



Plug & Play



Operator cabin

Safeway B.V.

Baanhoekweg 16, 3313 LA Dordrecht, The Netherlands
info@safewaygangway.com
www.safewaygangway.com

PART OF  **VAN AALST GROUP**

Safeway B.V. operates under the certified Quality, Health, Safety and Environmental management systems of the Van Aalst Group (ISO 9001, ISO 14001, ISO 45001).



Quality management



Working healthily & safely



Environmental management system